

BE version: rear shaft 13mm- 2x M2.5 on diam. 19.05 mm

### Characteristics

STEP ANGLE  
0,9°

STEP ANGLE ACCURACY  
± 5%

INSULATION CLASS  
B

AMBIENT TEMPERATURE  
-20°C +50°C

TEMP. RISE  
80°C MAX (RATED CURRENT, 2 PHASE ON)

INSULATION RESISTANCE  
100 M OHM MIN. 500 VDC

DIELECTRIC STRENGTH  
500 VAC FOR ONE MINUTE

SHAFT RADIAL PLAY  
0,02 MAX (450 G LOAD)

SHAFT AXIAL PLAY  
0,08 MAX. (450 G LOAD)





MAX RADIAL FORCE  
28 N (20 MM FROM FRONT FLANGE)

MAX AXIAL FORCE  
10 N

### Specification

Model		42SH33-1AM	42SH33-2AM	42SH33-3AM	42SH33-4AM	
1	RATED VOLTAGE	V	4	6	12	2,8
2	CURRENT/PHASE	A	0,95	0,6	0,31	1,33
3	RESISTANCE/PHASE	$\Omega$	4,2	10	38,5	2,1
4	INDUCTANCE/PHASE	mH	4	9,5	33	4,2
5	HOLDING TORQUE	NM	0,158	0,158	0,158	0,22
6	ROTOR INERTIA	G-CM <sup>2</sup>	35	35	35	35
7	WEIGHT	KG	0,22	0,22	0,22	0,22
8	NUMBER OF LEADS	N°	6	6	6	4

### Speed vs. Torque Characteristics



### Connection

LEAD N°	COLOR	GAUGE	FUNCTION
1	BLACK	UL1430 AWG26	PHASE A
2	GREEN	UL1430 AWG26	PHASE A-
3	RED	UL1430 AWG26	PHASE B
4	BLUE	UL1430 AWG26	PHASE B-
<b>UNIPOLAR MOTOR</b>			
5	YELLOW	UL1430 AWG26	COM PHASE A
6	WHITE	UL1430 AWG26	COM PHASE B

