

## SPECIFICATION


Model	573P79	
1 RATED VOLTAGE	V	6
2 CURRENT/PHASE	A	5,8
3 RESISTANCE/PHASE	Ω	1,05
4 INDUCTANCE/PHASE	mH	2,4
5 HOLDING TORQUE	Nm	1,5
6 ROTOR INERTIA	g-cm <sup>2</sup>	480
7 WEIGHT	Kg	1,1
8 NUMBER OF LEADS		6
9 LENGTH	mm	79

## CHARACTERISTICS

STEP ANGLE	1,2°
STEP ANGLE ACCURACY	± 5%
INSULATION CLASS	B
AMBIENT TEMPERATURE	-20°C +50°C
MAX TEMP. RISE (RATED CURRENT, 2 PHASE ON)	80°C
INSULATION RESISTANCE	100 Mohm min. 500 VDC
DIELECTRIC STRENGTH	500 VAC FOR ONE MINUTE
MAX SHAFT RADIAL PLAY (450 g LOAD)	0,02 mm
MAX SHAFT AXIAL PLAY (450 g LOAD)	0,08 mm
MAX RADIAL FORCE (20 mm FROM FRONT FLANGE)	75 N
MAX AXIAL FORCE	15 N

## CONNECTION

Pin N°	Color	Gauge	Function
1	RED	UL1430 AWG26	PHASE U
2	ORANGE	UL1430 AWG26	PHASE U
3	WHITE	UL1430 AWG26	PHASE V
4	BLUE	UL1430 AWG26	PHASE V
5	YELLOW	UL1430 AWG26	PHASE W
6	GREEN	UL1430 AWG26	PHASE W



573P79 VM: 35V; 5,0A /Phase

