



|                    |               |
|--------------------|---------------|
| Thread code:UKGI   |               |
| Thread type        | ACME          |
| Major diameter(mm) | 6.604...6.960 |
| Minor diameter(mm) | 4.763...4.943 |
| Lead               | 6.350         |
| Pitch              | 1.5875        |
| Starts             | 4             |
| Thread per inch    | 16            |

|   |  |  |  |                              |  |                     |  |
|---|--|--|--|------------------------------|--|---------------------|--|
| General tolerances<br>ISO 2768-m                  |  |  |  | Work piece edges<br>DIN 6784 |  | Scale:3:1           |  |
| Datum   |  |  |  | Name                         |  | Material: POM       |  |
| DRN 2017/11/16                                    |  |  |  | L W                          |  | external linear nut |  |
| CHKD 2017/11/16                                   |  |  |  | X T                          |  |                     |  |
| APVD 2017/11/16                                   |  |  |  | A.N.                         |  |                     |  |
| <b>Nanotec</b><br><small>PLUG &amp; DRIVE</small> |  |  |  |                              |  | LSNUT-AAAE-UKGI     |  |
| Rev   |  |  |  |                              |  | 1                   |  |
| Description                                       |  |  |  |                              |  | A3                  |  |
| Date  |  |  |  |                              |  |                     |  |
| Name  |  |  |  |                              |  |                     |  |